



MC-5L316B



Cost-Efficiency Excellence

Eco-Efficient Cooling


R600a (HC)refrigerant:Near-zero GWP

Energy consumption: $\leq 2.5\text{ kWh}/24\text{h}$


Precision Temp. Control

Uniformity of $\pm 1.5^\circ\text{C}$: Ensures sample integrity throughout the chamber


■ Top Cooling



■ Built-in Air Duct




■ DC Turbo Fan



Multiple Alarm

Multiple alerts (audible/visual)
/sensor/high/low temp/low battery
Ambient




Electrically Heated Glass Door


Forced-Air Cooling No Frost



Built-in Handle



Application, Rating, & Electrical Data	
Application	Pharmacy refrigerator
Storage Volume (L/Cu.Ft)	316/11.16
Temperature Range	+2°C to +8°C
Default Set Point	+5°C
Power Supply	220-240V/50Hz
Current	1.5A
Power Cord Length	1.7m
Certification	CE
Door type	Electrically Heated Glass Door
Application Environment	Non-corrosive, non-flammable, non-explosive
Ambient Operating Temperature	+16°C to +32°C
Refrigeration	
Refrigeration System	Forced-air/hydrocarbon Refrigerant
Compressor	Hermetic
Condenser Type	Built-in
Expansion Device	Cap tube
Evaporator Type	Fin and tube
Defrost Method	Automatic
Refrigerant	R600a
Controller / Configuration Settings	
Display screen	LED
Controller Type	Microprocessor
Security	Lockable door, password protected settings
High/Low Alarms	Yes, fully adjustable
Door Ajar Alarm	Yes, fully adjustable
Min/Max Temperature	Yes, display and reset
Dimensions and Construction	
Interior (w*d*h)	500*464*1343 mm
Exterior (w*d*h)	595*603*1920 mm
Access Port	Access Port- for external monitoring probe(s) (25 mm diameter)
Shelves	5 35 kg max capacity/drawer
Wheels	4, The front two can be stopped
Net Weight	68 kg
Gross Weight	76 kg



Typical Temperature Map

	test1	test2	test3	test4	test5	test6	test7	test8	test9
Avg	4.88	5.24	5.15	4.13	4.32	4.92	4.71	4.78	5.37
Max	5.30	5.60	5.50	4.80	4.70	5.20	5.00	5.10	5.70
Min	4.40	4.90	4.70	3.50	4.00	4.60	4.40	4.40	5.10

Location of test probes

Performance Characteristics (normal operating conditions)	
Uniformity (°C)	±1.5
Recovery to 8°C after 1 min door opening (min)	9
Temperature fluctuation (°C)	≤2
Energy consumption (kWh/day)	2.5
Noise emission (dB)	45
Heat rejection (BTU/hr)	870
Pull-down time to 6°C (min)	90

All performance data from 316L refrigerator, 25 ambient, 5.0°C

